



# MVP Hydra Specifications



**MVPH1**



**MVPH2**



**MVPH3**

**Electrical**

**Steam**

**Brew**

	Voltage, Single Phase	Amps, Max Draw	Cord Plug Rating, Amps (UL)	Watts per Element	Total Wattage	Tank Capacity, Liters	Watts per Element	Total Wattage	Tank Capacity, Liters
<b>1-Group</b>	220	16	20	1000 x 2	2000	3.2	700	700	1.9
<b>2-Group</b>	220	30	30	2000 x 2	4000	7.7	700 x 2	1400	1.9 x 2
<b>3-Group</b>	220	40	50	2500 x 2	5000	12.3	700 x 3	2100	1.9 x 3

**Machine Dimensions**

**Plumbing**

	Height	Width (Inch / mm)	Depth	Machine Weight (Lbs / Kgs)	Shipping Weight (Lbs / Kgs)	Shipping Dimensions L x W x H (Inch / mm)	Direct Connection (Compression)
<b>1-Group</b>	21 / 534	19 / 483	24 / 610	106 / 48	228 / 103	33 x 36 x 30 / 838 x 914 x 762	3/8" OD
<b>2-Group</b>	21 / 534	30 / 762	24 / 610	154 / 70	309 / 140	33 x 36 x 30 / 838 x 914 x 762	3/8" OD
<b>3-Group</b>	21 / 534	41 / 1042	24 / 610	190 / 86	387 / 176	33 x 46 x 30 / 838 x 1168 x 762	3/8" OD

- Certified by Intertek (ETL) for Sanitation to NSF / ANSI 4
- Certified by Intertek (ETL) for Electrical Safety to ANSI / UL 197
- Certified by Intertek (ETL) for Electrical Safety to CSA C22.2 No. 109
- Certified by KTR for Korean KC Mark
- Certified to IECEE CB Scheme
- CE Compliant (By request)
- C-Tick Compliant (By request)
- Sabre Compliant (By request)

