



# S-Series Specifications



**S200**



**S300**

**Electrical**

**Steam**

**Brew**

	Voltage, Single Phase	Amps, Max Draw	Cord Plug Rating, Amps (UL)	Watts per Element	Total Wattage	Tank Capacity, Liters	Watts per Element	Total Wattage	Tank Capacity, Liters
<b>2-Group</b>	220	28	30	2000 x 2	4000	7.7	700 x 2	1400	1.9 x 2
<b>3-Group</b>	220	36	50	2500 x 2	5000	12.3	700 x 3	2100	1.9 x 3

**Machine Dimensions**

**Plumbing**

	Height	Width (Inch / mm)	Depth	Machine Weight (Lbs / Kgs)	Shipping Weight (Lbs / Kgs)	Shipping Dimensions L x W x H (Inch / mm)	Direct Connection (Compression)
<b>2-Group</b>	16.9 / 428	27.6 / 702	24 / 610	152 / 69	247 / 112	33 x 36 x 30 / 838 x 914 x 762	3/8" OD
<b>3-Group</b>	16.9 / 428	37 / 940	24 / 610	225 / 102	320 / 145	33 x 46 x 30 / 838 x 1168 x 762	3/8" OD

- Certified by Intertek (ETL) for Sanitation to NSF / ANSI 4
- Certified by Intertek (ETL) for Electrical Safety to ANSI / UL 197
- Certified by Intertek (ETL) for Electrical Safety to CSA C22.2 No. 109
- Certified by KTC for Korean KC Mark
- Certified to IECEE CB Scheme
- CE Compliant (By request)
- C-Tick Compliant (By request)
- Sabre Compliant (By request)

